



Folder

Terry folder

FTI3

<u>Dimensions*</u>		<u>Machine*</u>	<u>Package*</u>
Width*	mm	2420	2300
Depth*	mm	4245	3900
High*	mm	1425	1625
Weight*	Kg	1450	1700
Volume*	m ³	14,64	14,58

<u>Length folds</u>		<u>Crossfold</u>	
Lanes	Folds	Lanes	Folds
1	1-2	1	1-2
-	(1/2) - (1/3)	-	(1/2) - (1/2)(1/3)

Items selection	Automatico
Folding cycle medium time	4/5 sec.
Medium production	850 Pz/h
Item to fold max dimensions**	1200 x 2000 mm
Item to fold minimum dimensions	480 x 480 mm
Folding belts speed 50 m/min	
Program.logic control (PLC) that allows to fold the linen according to its dimensions and to create 20 working programs	
Touch- screen control panel	
Side exit on conveyor (rh-lh), front or back	
Crossfold by-pass	
Length fold by air jets	
Crossfold by air jets and rotating rolls	
Automatic reject too large items	
Compact machine: max surf. less than 10 sqm	

Optional (to define at the order)

- √ Dirty and ripped linen reject
- √ Supply different than 400V ~3N + T - 50Hz

Electrical installation*

Electrical power	kW	2,6 *
Voltage 400V ~3N + T	A	11,1 *
Voltage 230V ~3 + T	A	11,1 *


Pneumatic installation*

Compressed air needed bar	7	25000	NI/h
---------------------------	---	-------	------

Livello intensità sonora area

<80 dB(A)

<u>Connections</u>	<u>Compressed air</u>	<u>Electricity</u>	<u>Gas/Steam</u>	<u>Exhaust fume</u>	<u>Exhaust (Steam)</u>
Type	Ø 12 mm	5G4-400V	-	-	-
X mm	80	1350	-	-	-
Y mm	0	0	-	-	-
Z mm	85	85	-	-	-



Heating

<u>Natural gas</u>			<u>LPG</u>			<u>Steam (P max 12 bar)</u>			<u>Electrical</u>		
Consumption	m ³ /h	-	Consumption	m ³ /h	-	Consumption	Kg/h	-	Consumption	A	-
Power	kW	-	Power	kW	-	Power	kW	-	Power	kW	-

*) Optional excluded **) For larger dimensions on request

The technical data can change without advice

rev.06